

REFERENCES

- Abbey, T. *et al.* (2018) 'An Embedded Environmental Control Micro-chamber System for RRAM Memristor Characterisation', pp. 33–36.
- Arif, A. Bin (2016) 'METODE ACCELARATED SHELF LIFE TEST (ASLT) DENGAN PENDEKATAN ARRHENIUS DALAM PENDUGAAN UMUR SIMPAN SARI BUAH NANAS , PEPAYA DAN CEMPEDAK Accelerated Shelf Life Test (ASLT) Method With Arrhenius Approach for Shelf Life Estimation of Pineapple , Papaya And Cempedak Juices', pp. 189–198.
- Ashara, G. S. and Vyas, D. S. (2015) 'Design and Simulation of Temperature Control of Chamber Based on Automatic Fan Speed Control', *International Journal of Advance Engineering and Research Development*, 3(02), pp. 1–4. doi: 10.21090/ijaerd.i1066905.
- Astrom, Karl J and Hagglund, T. (1988) *PID COntrollers: theory, Design, and Tuning*.
- D, M. K., B, M. S. and S, R. K. (2014) 'Analysis of TOI (Things of Internet) Industrial Monitoring System on Raspberry pi Platform', 2, pp. 33–40.
- Darehshouri, S. *et al.* (2020) 'A low-cost environmental chamber to simulate warm climatic conditions', *Vadose Zone Journal*, 19(1), pp. 1–6. doi: 10.1002/vzj2.20023.
- Domínguez, G. E. *et al.* (2017) 'Development of a system for measuring and controlling environmental parameters in an chamber for in vitro cell cultures experimentation', pp. 3–6.
- Enjing, Z. *et al.* (2014) 'The design of temperature control system of test chamber based on predictive control algorithm', *Proceedings - 2014 4th International Conference on Instrumentation and Measurement, Computer, Communication and Control, IMCCC 2014*, pp. 226–229. doi: 10.1109/IMCCC.2014.54.
- Ezike, S. C. (2018) 'A Low-Cost Temperature-Controlled Chamber'. doi:

10.3390/designs2030025.

Feng, J. *et al.* (2015) 'Development of a low-cost and vibration-free constant-temperature chamber for precision measurement', *Sensors and Materials*, 27(4), pp. 329–340. doi: 10.18494/SAM.2015.1071.

van Geel, J. L. W. A. *et al.* (2014) 'Thermistors Used in Climatic Chamber at High Temperature and Humidity', *International Journal of Thermophysics*, 36(2–3), pp. 569–576. doi: 10.1007/s10765-014-1753-7.

Leskinen, A. *et al.* (2015) 'Characterization and testing of a new environmental chamber', pp. 2267–2278. doi: 10.5194/amt-8-2267-2015.

M, S. M., Srikanth, L. and Vps, N. (2017) 'Design and Development of LabVIEW based Environmental Test Chamber Controller', pp. 0–3.

Mensah, K. and Choi, J. M. (2017) 'Energy consumption and stability investigation of constant temperature and humidity test chamber', *International Journal of Air-Conditioning and Refrigeration*, 25(1), pp. 1–11. doi: 10.1142/S2010132517500109.

Nasution, H. (2007) 'ENERGY ANALYSIS OF AN AIR CONDITIONING SYSTEM USING PID AND FUZZY LOGIC CONTROLLERS', *Int.*

Pulungan, M. H. (2016) 'Penentuan Umur Simpan Pia Apel dengan Metode ASLT (Studi Kasus Di UMKM Permata Agro Mandiri Kota Batu) Shelf Life Prediction of Apple Pia using ASLT Method (Case Study In Smes (Small And Medium Enterprise) Permata Agro Mandiri Batu', 5(2), pp. 61–66.

Rrg, Q., & Gudwru, H. K. (n.d.). ,qgxfwlrq)rrg 'hk\gudwru zlwk 7hpshudwxuh &rqwuro. 9–12.

Sensortec, B. (2013) 'Digital pressure sensor', (April).

Sharifi, S., Liu, C. C. and Rosing, T. S. (2008) 'Accurate temperature estimation for efficient thermal management', *Proceedings of the 9th International Symposium on Quality Electronic Design, ISQED 2008*, pp. 137–142. doi: 10.1109/ISQED.2008.4479714.

Song, W. K. *et al.* (2013) 'Development of a Large-Scale Environmental Chamber for Investigating Soil Water Evaporation', *Geotechnical Testing Journal*, 36(6). doi: 10.1520/GTJ20120142.

Vatsal, S. and Bhavin, M. (2017) 'USING RASPBERRY PI TO SENSE TEMPRATURE AND RELATIVE HUMIDITY', pp. 380–385.

Wang, L., Freeman, C. and Rogers, E. (2001) 'Experimental Evaluation of Automatic Tuning of PID Controllers for an Electro-Mechanical System'.

Zungeru, A. M. *et al.* (2018) 'Design and simulation of an automatic room heater control system', *Heliyon*. Elsevier Ltd, 4(6), p. e00655. doi: 10.1016/j.heliyon.2018.e00655.