

REFERENCES

- (n.d.). Retrieved from What is osteoarthritis? | Arthritis Research UK: <http://www.arthritisresearchuk.org/arthritis-information/conditions/osteoarthritis/what-is-osteoarthritis.aspx>
- (n.d.). Retrieved from National Institute of Health: <https://www.nlm.nih.gov/medlineplus/ency/article/003929.htm>
- (1977). Retrieved from Stairplan: <http://www.stairplan.co.uk/regulations.htm>
- Abbas, S. J., & Abdulhassan, Z. M. (2013). Kinematic Analysis of Human Climbing up and Down. *Eng. & Tech. Journal, Vol. 31, Part (A), No.8, 2013* 2.
- Adipurra, D., Mazlan, S., Zamzuri, H., & Rahman, M. A. (2016). Fuzzy Logic Controller for Current Induced Ankle. *Journal of Advanced Vehicle System*, 28-40.
- Albertos, P., & Sala, A. (1998). Fuzzy Logic Controllers. Advantages and Drawbacks.
- Alves, A. O. (2012, September 28). zerokol.com. Retrieved from eFLL - A Fuzzy Library for Arduino and Embedded Systems: <http://www.zerokol.com/2012/09/arduino-fuzzy-fuzzy-library-for-arduino.html>
- Arduino Mega . . (n.d.). Retrieved from ArduinoBoardMega2560: <https://www.arduino.cc/en/Main/ArduinoBoardMega2560>
- Banks, W., & Hayward, G. (2002). *Fuzzy Logic in Embedded Microcomputers and Control System*. Waterloo: Byte Craft Limited.
- Bortole, M. (2013). *DESIGN AND CONTROL OF A ROBOTIC EXOSKELETON FOR GAIT REHABILITATION*. MADRID: Undergraduate. UNIVERSIDAD CARLOS III DE MADRID.
- Calin, D. G. (2014). *Overview of Exoskeleton Suits - Assistant, Paralyzed, And Military Exoskeletons*. Retrieved from <http://www.intorobotics.com/overview-of-exoskeleton-suits-assistant-paralyzed-and-military-exoskeletons/>
- Campellone, J. (n.d.). *Electromyography: MedlinePlus Medical Encyclopedia*. Retrieved from nlm.nih.gov

Costanzo, L. S. (2011). *Physiology*. Philadelphia: Wolters Kluwer Health/Lippincott Williams & Wilkins.

De Luca, C. J. (1997). The Use of Surface Electromyography in Biomechanics. *Journal of applied biomechanics*, 13, 135-163.

Difference between Aluminum and Stainless Steel. (2014). Retrieved from TheyDiffer.com: <http://theydiffer.com/difference-between-aluminum-and-stainless-steel/>

Drillis, R., & Contini, R. (1966). *Body Segments Parameters*. New York: Office of Vocational Rehabilitation, Department of Health, Education and Welfare.

Engineers Edge. (2002). Retrieved from Engineers Edge: Worm Gear Formula Table: http://www.engineersedge.com/gears/worm_gear_formula_table_13534.htm

Fuchs, C. (2010). Demografischer wandel und notwendigkeit der priorisierung im gesundheitswesen. Positionsbestimmung der Ärzteschaft". *Bundesgesundheitsbl Gesundheitsforsch Gesundheitsschutz*, vol 83, 435-440.

Godjevac, J. (n.d.). Comparison Between PID and Fuzzy Control. 25-36.

Gravlee, J. R., & Van Durme, D. J. (2007). Braces and Splints for musculoskeletal conditions. *Article of American Family Physician*, 75 (3), 342-348.

Hayashi, T., Kawamoto, H., & Sankai, Y. (2005). Control Method of robot suit HAL working as operator's muscle using biological and dynamical information. *Intelligent Robots and Systems, (IROS). Proceedings of the 2005 IEEE/RSJ International Conference on*, 3063-3068.

Homola, S., & D.C. (2015). *Dubious Use of Surface Electromyography (SEMG)*. Retrieved from <http://chirobase.org/06DD/semg.html>

Inverarity, L. D. (2014). *The Gait Cycle*. Retrieved from About.com Health.

Jones, R. V. (2001). *Electronic Devices and Circuits: Diode Applications*. Retrieved from http://people.seas.harvard.edu/~jones/es154/lectures/lecture_2/diode_circuits/diode_appl.html

- Kawamoto, H., & Sankai, Y. (2002). Comfortable power assist control method for walking aid by HAL-3. *Systems, Man and Cybernetics, 2002 IEEE International Conference on* (Volume:4).
- Kawamoto, H., & Sankai, Y. (2002). Power Assist System HAL-3 for Gait Disorder Person. *ICCHP*, 196-2003.
- Kelley, L. C. (1919). *USA Patent No. 1308675*.
- Kharb, A., Saini, Y., Jain, Y. K., & Dhiman, S. (2011). Review of Gait Cycle and Its Parameters. *International Journal of Computational Engineering and Management* (13), 78-83.
- Khuman, P. R. (2012, June). *Gait Normal and Abnormal*. Retrieved from <http://www.slideshare.net/prkhuman/gait-normal-abnormal>
- Kidarsa, L. A. (2005). *ANALISIS GERAKAN ORANG BERJALAN DAN PERANCANGAN PROTOTIPE PROTESIS KAKI*. Bandung.
- Kneip, L. (2015). *ECG Analyser*. Retrieved from Laurentkneip.de: http://www.laurentkneip.de/ECG_analyser_files/content.html
- Kozlowska, E. (2012, September 1). *Basic Principle of Fuzzy Logic*. Retrieved from Access Server: <http://access.feld.cvut.cz/view.php?cisloclanku=2012080002>
- Lee, S., & Sankai, Y. (2002). Power Assist Control for Walking Aid with HAL-3 Based on EMG and Impedance Adjustment Around Knee Joint. *Intelligent Robots and Systems. IEEE/RSJ International Conference on* (Volume:2), 1499-1504.
- Liu, X., & Low, K. H. (2004). Development and Preliminary Study of the NTU Lower Extremity Exoskeleton. *Cybernetics and Intelligent Systems, 2004 IEEE Conference on* (Volume:2), 1242-1246.
- Mancini, R. (2005). *So Many Amplifiers to Choose From*. Retrieved from <http://www.ti.com/lit/an/slyt213/slyt213.pdf>,
- McManis, C. (n.d.). *H-Bridge Theory & Practice -- Chuck's Robotics Notebook*.
- Mechanical Design Data Manual*. (2000). Manufacturing and Engineering Educational Services, N.S.W. TAFE Commission.
- Morris, C., & Dias, L. S. (2007). *Paediatric Orthotics*. Oxford: Mac Keith Press.

Nishihara, K., & Isho, T. (2012). Location of Electrodes in Surface EMG. In M. M. Schwartz (Ed.), *EMG Methods for Evaluating Muscle and Nerve Function*. InTech. Retrieved from <http://www.intechopen.com/books/emg-methods-for-evaluating-muscle-and-nerve-function/location-of-electrodes-in-surface-emg>

Novak, A. M., Reid, S. M., Costigan, P. P., & Brouwer, B. P. (2000, October). *Stair Negotiation alters stability in older adults*. Retrieved from Lower Extremity Review: <http://lermagazine.com/article/stair-negotiation-alters-stability-in-older-adults>

Physiopedia. (n.d.). *Gait*. Retrieved from Physiopedia: <http://www.physiopedia.com/Gait>

Rahmat, M. F., & Ghazaly, M. M. (2006). Performance Comparison Between PID and Fuzzy Logic Controller In Position Control System of DC Servomotor. *Jurnal Teknologi*.

Ryan, V. (2002). Retrieved from Worm Gears: <http://www.technologystudent.com/gears1/worm1.htm>

Simmons, J. (n.d.). *The Sarcomere and Sliding Filaments in Muscular Contraction: Definition and Structures*. Retrieved from <http://study.com/academy/lesson/the-sarcomere-and-sliding-filaments-in-muscular-contraction-definition-and-structures.html>

Smith, M. (2014). *Bionic Humans: Exoskeleton Technology Is Redefining Limits*. Retrieved from MakeUsOf: <http://www.makeuseof.com/tag/bionic-humans-exoskeleton-technology-redefining-limits/>

Stair Climbing. (2008). Retrieved from <http://courses.washington.edu/anatomy/KinesiologySyllabus/Stairs2008.pdf>

Tantos, A. (2011). *H-Bridges - The Basics*. Retrieved from <http://www.modularcircuits.com/blog/articles/h-bridge-secrets/h-bridges-the-basics/>

Taylor, T. (n.d.). *Muscular System*. Retrieved from <http://www.innerbody.com/image/musfov.html>

- Thakor, N. (1999). Biopotential and Physiology Measurement. In *In The Measurement, Instrumentation, and Sensors Handbook*. Boca Raton, FL, USA: CRC Press LLC.
- Timings, R. (2005). *Mechanical Engineer's Pocket Book, 3rd Edition*. Newnes.
- Todd, F. (n.d.). Retrieved from Clinicalgaitanalysis.com
- Viitasalo, J., & Komi, P. (n.d.). Signal Characteristics of Emg during fatigue. *European Journal of Applied Physiology* 37, 111-121.
- Vukobratovic, M., & Juricic, D. (1969). Contribution to the synthesis of biped gait. *IEEE Transactions on Bio-Medical Engineering, BME-16*, No. 1., 1-6.
- Webster, J., & Clark, J. (2010). *Medical Instrumentation: Application and Design*. Hoboken, NJ: John Wiley & Sons.
- Whittle, M. (2007). *Gait Analyis*. Edinburgh: Butterworth-Heinemann.
- Whittlesey, S. N., & Hamil, J. (1996). An Alternative Model of the Lower Extremity During Locomotion. *Journal of Applied Biomechanics*, 269-279.
- Wille, F., Knoll, A., & Zhang, J. (n.d.). Fuzzy Logic Rules for Mapping Sensor Data to Robot Control. *Faculty of Technology, University of Bielefeld*.
- Winter, D. A. (2009). *Biomechanics and motor control of human movement*. Wiley.
- Yagin, N. (1890). *United States of America Patent No. 440684*.
- Yakimovich, T., Kofman, J., & Lemaire, E. D. (2006). Design And Evaluation of a stance control knee ankle foot orthosis knee joint. *IEEE Transactions on Neural Systems and Rehabilitation Engineering* 14(3), 361-369.
- Yakimovich, T., Lemaire, E. D., & Kofman, J. (2009). Engineering Design review of stance-control knee-ankle-foot-orthoses. *Journal of Rehabilitation Research & Development*, 46(2), 257-268.
- Zhang, Y., Behrens, S., & Finger, S. (n.d.). Retrieved from Introduction to Mechanisms.: <https://www.cs.cmu.edu/~rapidproto/mechanisms/chpt7.html>
- Zoss, A., & Kazerooni, H. (2006). Design Of An Electrically Actuated Lower Extremity Exoskeleton. *Advanced Robotics*, 20(9), 967-988.